


PROJECT NAME:

TYPE:




3" _____


	SHAPE	VERSION	TRIM	FRAME FINISH	REFLECTOR FINISH	LED CHIP	CRI/LUMENS	CCT	BEAM ANGLE	DIMMING	ACCESSORIES
3 INCH	R Round	05	QS Microflange QT Trimless Drywall	B Black W White	B Black W White G Gold	B Bridgelux	90 90+ CRI 15 Watts Lumens Divd.-1380	27  2700K 30  3000K 35  3500K 40  4000K	35 35°	CMEM55 On/Off; Triac PhaseDim; 120VAC KIG On/Off; Triac Phase Dim; 120/277VAC *Remote Placed	NCP-SR3-R21 Non-IC Bracket NCBX-SR3-R21 IC Box BRKT-2SR75A Non-IC Bracket for Dual Lights *For more details,pls refer to page 3
							97 97+ CRI 15 Watts Lumens Divd.-945		35 35°		
							Dim To Warm				
							90 90+ CRI 15 Watts Lumens Divd.-750	1830  1800-3000K	35 35°		
							90 90+ CRI 15 Watts Lumens Divd.-1150 *External 5CCT Selector	2765A  2700K  3000K  4000K  5000K  6500K	35 35°		
TUNABLE WHITE											
							90 90+ CRI 15 Watts Lumens Divd.-1150	2765  2700-6500K	25 25°	*Dali 2ch Driver Remote Placed	
3 Inch Recessed Round Adjustable Spotlight											

Photometry

Beam angle: 35°
Delivered Lumens: 1380 lumens
CCT: 4000K
CRI: 90
Power: 15W
Efficacy: 92lm/W





Beam angle: 25°
Delivered Lumens: 945 lumens
CCT: 4000K
CRI: 97
Power: 15W
Efficacy: 63lm/W



ACCESSORIES

Brackets for New-Construction (4-legs)





Cut out:

Round: Ø 3" (Ø 77mm)
Ø 2" (Ø 62mm)
Ø 1" (Ø 50mm)

Square: □ 3" (□ 77mm)

IC-BOX for New-Construction (4-legs)







Cut out:

Round: Ø 3" (Ø 77mm)
Ø 2" (Ø 62mm)
Ø 1" (Ø 50mm)

Square: □ 3" (□ 77mm)

Cut out




Brackets for New-Construction



Cut out:

Round: Ø 77mm*2 (Ø 77mm*2)

Square: □ 77mm*2 (□ 77mm*2)



Remark




Tailored brackets are available with a reasonable surcharge, details as below

- The customized bracket dimensions are still the same as the existing ones, 600*200mm
- Hole sizes can be customized within the range of 25-100mm
- Holes quantity can be indicated, 1-7pcs
- Holes' positions on the bracket can be done as requests




NOURDIC LIGHTING COMPANY

Locations: USA: 485 Glenbrook Dr, Lake Worth, FL 33462
Canada: 480 Warren Rd, King City ON L7B 1C4




E: info@nuordic.com
T: +1-561-695-4107



D1:min. 0.06" (1.5mm)
D2:max.0.94" (24mm)



Microflange



Trimless Drywall

